



R32 SUPER MATCH MULTI SISTEMI

Multi split klima uređaji Haier pravi su odabir za one koji žele klimatizovati više prostorija u domu ili u objektima komercijalne namene.

Predstavljaju idealno estetsko i konstrukcijsko rešenje za grejanje i hlađenje više prostorija: za veće stambene ili poslovne prostore, apartmane, hotele, restorane itd.

Opcije unutrašnjih jedinica su zidna, kasetna i podna, različitih raspona snage, zavisno od preferencija i potreba korisnika.

- unutrašnje jedinice mogu biti različitih tipova ugradnje i međusobno različitih kapaciteta
- individualno upravljanje ili grupno



PREGLED MODELA

SERIJA	2,5 kW	3,5 kW
Expert	 AS25XCAHRA	 AS35XCAHRA
Flexis Plus	 AS25S2SF1FA-WH S25S2SF1FA-S AS25S2SF1FA-BH	 AS35S2SF1FA-WH AS35S2SF1FA-S AS35S2SF1FA-BH
Pearl	 AS25PBAHRA	 AS35PBAHRA
Tundra	 AS25TAEHRA-THC	 AS35TADHRA-THC
Tide	 AS25THMHRA-C	 AS35TAMHRA-C



Multi split R32

5 kW	7,1 kW	
 AS50XCAHRA		
 AS50S2SF1FA-WH AS50S2SF1FA-BH	 AS71S2SF1FA-WH AS71S2SF1FA-BH	
 AS50PDAHRA	 AS68PDAHRA	
 AS50TDDHRA-THC	 AS68TDRHRA-THC	
 AS50TDMHRA-C	 AS68TDRHRA-C	

PREGLED MODELA

SERIJA	2,5 kW		3,5 kW	
Kompaktni kasetni model - mini (panel: PB620 KB(H))	 AB25S2SC2FA (H)	 AB35S2SC2FA (H)		
Kompaktni kasetni model - (panel: PB620 KB(H))	 AB25S2SG2FA (H)	 AB35S2SG2FA (H)		
360° kasetni model PB-950QB(H)				
Slim kanalski model (niski ESP)	 AD25S2SS1FA(H) Panel: P1B-890IA/D (opcija)	 AD35S2SS1FA(H) Panel: P1B-890IA/D (opcija)		
Slim kanalski model (srednji ESP)		 AD35S2SM9FA(H)		
Podnoplafonski model		 AC35S2SG2FA(H)		
Podni inverter model	 AF25S2SD1FA(D)	 AF35S2SD1FA(D)		
	5,0 kW	5,5 kW	7,0 kW	7,5 kW
SPOLJAŠNJE JEDINICE	 2U50S2SM1FA-3	 3U55S2SR5FA	 3U70S2SR5FA	 4U75S2SR5FA



Multi split R32

4,2 kW		5 kW		7,1 kW			
		 AB50S2SC2FA (H)					
		 AB50S2SG2FA (H)					
				 AB71S2SR1FA(H)			
		 AD50S2SS1FA (H) Panel: P1B-1210IA/D (opcija)		 AD71S2SS1FA (H) Panel: P1B-1210IA/D (opcija)			
		 AD50S2SM9FA(H)		 AD71S2SM9FA(H)			
		 AC50S2SG2FA(H)		 AC71S2SG2FA(H)			
 AF42S2SD1FA(D)							
8,5 kW		9,0 kW		10,5 kW		12,5 kW	
 4U85S2SR5FA		 5U90S2SS5FA		 5U105S2SS5FA		 5U125S2SN1FA	

Multi inverter



Model		2U50S2SM1FA	3U55S2SR5FA	3U70S2SR5FA
Maksimalan broj unutrašnjih jedinica		2	3	3
Kapacitet - hlađenje	kW	5.0	5.0 (2.1-6.6)	7.0 (2.4-7.6)
Kapacitet - grejanje	kW	5.7	6.4 (1.7-7.2)	7.6 (2.9-8.5)
SEER / SCOP		6.5/4.0	8.5/4.6	8.5/4.6
Energetska klasa (grejanje / hlađenje)		A++/A+	A+++/A++	A+++/A++
Napajanje	Ph/V/Hz	1/230/50		1/220-240/50/60
Protok vazduha (H/M/L)	m³/h	2200	≈3000	≈3000
Nivo buke - zvučna snaga H/M/L	db(A)	62	64	66
Nivo zvučnog pritiska H/M/L	db(A)	56	51	53
Spoljašnje dimenzije Š/D/V	mm	800/275/553	890/340/700	890/340/700
Neto / Bruto težina	kg	34/37	50/59	54/63
Freon		R32	R32	R32
Promer cevi tečni	mm	2×6.35	3×6.35	3×6.35
Promer cevi gasni	mm	2×9.52	3×9.52	3×9.52
Maksimalna dužina cevovoda	m	30	50	60
Maksimalna dužina cevovoda bez nadopune	m	20	30	30
Nadopuna po dodatnom metru	g/m	20	20	20
Maksimalna visinska razlika	m	15	15	15
Temperaturni raspon rada - hlađenje	°C	-10~46	-10~46	-10~46
Temperaturni raspon rada - grejanje	°C	-15~24	-15~24	-15~24
Razmak između nogica	mm	510	630	630

KOMBINACIJE SPAJANJA UNUTRAŠNJIH I SPOLJAŠNJIH JEDINICA

Multi R32					2 unutrašnje jedinice									3 unutrašnje jedinice							
Broj unutrašnjih jedinica	2	3	4	5	9	9	9	9	12	12	12	18	18	24	9	9	9	9	9	9	9
					9	12	18	24	12	18	24	18	24	24	9	9	9	9	12	12	12
					-	-	-	-	-	-	-	-	-	-	9	12	18	24	12	18	24
					-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
					-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Spoljašnja jedinica	2U50S2SM1FA				*	*			*												
	3U55S2SR5FA				*	*	*		*					*							
	3U70S2SR5FA				*	*	*		*	*				*	*			*			
	4U75S2SR5FA				*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	
	4U85S2SR5FA				*	*	*		*	*	*	*	*	*	*	*	*	*	*		
	5U90S2SS5FA				*	*	*	*	*	*	*	*	*	*	*	*	*	*	*		
	5U10S2SS5FA				*	*	*	*	*	*	*	*	*	*	*	*	*	*	*		
5U12S2SN1FA				*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*		

*Obavezno prije kupnje Multi invertera opcije (Super Match) potrebno je provjeriti tehničke specifikacije i mogućnosti instalacije s ovlaštenim Haier serviserima. Za detaljne informacije posjetite www.haier-klima.com.



Model		4U75S2SR5FA	4U85S2SR5FA	5U90S2SS5FA	5U105S2SS5FA	5U125S2SN1FA
Maksimalan broj unutrašnjih jedinica		4	4	5	5	5
Kapacitet - hlađenje	kW	7.6(2.4-8.7)	8.5(3.2-9.5)	9.0(3.2-11.0)	10(3.2-11.0)	12.5(3.2-13.8)
Kapacitet - grejanje	kW	8.6(3.1-10.0)	9.3(4.4-10.5)	10.4(4.4-11.5)	10.5(4.4-11.5)	12.7(4.4-14.3)
SEER / SCOP		7.0/4.2	7.0/4.2	7.0/4.2	7.0/4.2	7.10/4.05
Energetska klasa (grejanje / hlađenje)		A++/A+	A++/A+	A++/A+	A++/A+	A++/A+
Napajanje	Ph/V/Hz	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60	1/220-240/50/60
Protok vazduha (H/M/L)	m³/h	≈4000	≈4000	4200	4200	4200
Nivo buke - zvučna snaga H/M/L	db(A)	68	68	70	70	73
Nivo zvučnog pritiska H/M/L	db(A)	55	55	55	55	58
Spoljašnje dimenzije Š/D/V	mm	890/340/700	890/340/700	920/372/760	920/372/760	950/370/965
Neto / Bruto težina	kg	61/70	61/70	66/77	66/70	79/91
Freon		R32	R32	R32	R32	R32
Promer cevi tečni	mm	4×6.35	4×6.35	5×6.35	5×6.35	5×6.35
Promer cevi gasni	mm	3×9.52+1×12.7	3×9.52+1×12.7	3×9.52+2×12.7	3×9.52+2×12.7	3×9.52+2×12.7
Maksimalna dužina cevovoda	m	70	70	80	80	100
Maksimalna dužina cevovoda bez nadopune	m	40	40	40	40	50
Nadopuna po dodatnom metru	g/m	20	20	20	20	20
Maksimalna visinska razlika	m	15	15	15	15	15
Temperaturni raspon rada - hlađenje	°C	-10~46	-10~46	-10~46	-10~46	-10~46
Temperaturni raspon rada - grejanje	°C	-15~24	-15~24	-15~24	-15~24	-15~24
Razmak između nogica	mm	630	630	660	660	590

						4 unutrašnje jedinice										5 unutrašnjih jedinica				
12	12	12	12	12	18	9	9	9	9	9	9	9	9	9	12	9	9	9	9	9
12	12	12	18	18	18	9	9	9	9	9	9	12	12	12	12	9	9	9	9	9
12	18	24	18	24	18	9	9	9	9	12	12	12	12	12	12	9	9	9	9	9
-	-	-	-	-	-	9	12	18	24	12	18	12	18	24	12	9	9	9	12	12
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	9	12	18	12	18
*	*					*	*			*										
*	*	*	*	*		*	*	*		*	*	*			*					
*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	
*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	
*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*